

Model	Signal						Electrical			Env	Physical	
	Modulation Type	ISM Band Freq (MHz)	Max Data Rate (kbps)	Max Open Air Dist (km)	Tx Pwr Max (dBm)	Rx Sensitivity (dBm)	Rx / Tx Current (mA)	Stand-By Current	Pwr Supply (V)	Operating temp (C)	Interface	Dimensions LxWxH (mm)
<b>2.4GHz Transceiver Modules</b> (half duplex, uni-directional)												
RFM75-S	GFSK	2400-2483.5	2000		20				1.9~3.6	-55~115		17x8x3
<b>Sub-GHz LoRa™ Transceiver Modules</b> (selectable LoRa or FSK/OOK modem)												
RFM95W-915	LoRa	915	300	5~8	20	-148	12 / 120	0.2uA	1.8~3.7	-55~115	TTL	16x16x1.8
RFM96W-433	LoRa	433	300	5~8	20	-139	12/ 120	0.2uA	1.8~3.7	-55~115	TTL	16x16x1.8
<b>Sub-GHz 100mW Transparent Data-link Transceiver Modules</b>												
HM-TRLR-D-433	LoRa	433	115.2	5+	20	-139	20 / 130	2uA	3.3~5.5	-55~115	TTL	47x26
HM-TRLR-D-915	LoRa	915	115.2	5+	20	-139	20 / 130	2uA	3.3~5.5	-55~115	TTL	47x26
HM-TRLR-S-433	LoRa	433	115.2	5+	20	-139	16 / 130	2uA	2.4~3.6	-55~115	TTL	20x16x2
HM-TRLR-S-915	LoRa	915	115.2	5+	20	-139	16 / 130	2uA	2.4~3.6	-55~115	TTL	20x16x2
HM-TRP-433	LoRa	434	115.2	1+	20	-117				-55~115	TTL	20x16x2
HM-TRP-915	LoRa	915	115.2	1+	20	-117				-55~115	TTL	20x16x2

For more information, contact:

**AMATEK DESIGN**

[www.amatek.com](http://www.amatek.com)

+61 2 9411 3618

(Sydney, Australia)

Model	Signal						Electrical			Env	Physical	
	Modulation Type	ISM Band Freq (MHz)	Max Data Rate (kbps)	Max Open Air Dist (km)	Tx Pwr Max (dBm)	Rx Sensitivity (dBm)	Rx / Tx Current (mA)	Stand-By Current	Pwr Supply (V)	Operating temp (C)	Interface	Dimensions LxWxH (mm)
<b>Sub-GHz Transceiver Modules</b>												
<b>RFM69W-433</b>	(G)FSK/OOK	433	300	0.6	13	-120	16 / 45	0.1uA	1.8~3.6	-55~115	TTL	19.7x16x1.9
<b>RFM69W-915</b>	(G)FSK/OOK	915	300	0.6	13	-120	16 / 45	0.1uA	1.8~3.6	-55~115	TTL	19.7x16x1.9
<b>RFM69CW-433</b>	(G)FSK/OOK	433	300	0.6	13	-120	16 / 45	0.1uA	1.8~3.6	-55~115	TTL	16x16x1.9
<b>RFM69CW-915</b>	(G)FSK/OOK	915	300	0.6	13	-120	16 / 45	0.1uA	1.8~3.6	-55~115	TTL	16x16x1.9
<b>RFM69HW-433</b>	(G)FSK/OOK	433	300	1	20	-120	16 / 130	0.1uA	1.8~3.6	-55~115	TTL	19.7x16x1.9
<b>RFM69HW-915</b>	(G)FSK/OOK	915	300	1	20	-120	16 / 130	0.1uA	1.8~3.6	-55~115	TTL	19.7x16x1.9
<b>RFM69HCW-433</b>	(G)FSK/OOK	433	300	1	20	-120	16 / 130	0.1uA	1.8~3.6	-55~115	TTL	16x16x1.9
<b>RFM69HCW-915</b>	(G)FSK/OOK	915	300	1	20	-120	16 / 130	0.1uA	1.8~3.6	-55~115	TTL	16x16x1.9

**NOTES:**

RFM69W & RFM69CW are functionally the same. Only the pin-outs are different, with the RFM69CW compatible with older RFM12B modules

RFM69HW & RFM69HCW are functionally the same. Only the pin-outs are different, with the RFM69HCW compatible with older RM22B/RFM23B modules.

For more information, contact:

**AMATEK DESIGN**

[www.amatek.com](http://www.amatek.com)

+61 2 9411 3618

(Sydney, Australia)

Model	Signal						Electrical			Env	Physical	
	Modulation Type	ISM Band Freq (MHz)	Max Data Rate (kbps)	Max Open Air Dist (km)	Tx Pwr Max (dBm)	Rx Sensitivity (dBm)	Rx / Tx Current (mA)	Stand-By Current	Pwr Supply (V)	Operating temp (C)	Interface	Dimensions LxWxH (mm)
<b>Enhanced Power Sub-GHz Transceiver Module</b>												
RFM23BP-433	(G)FSK/OOK	433	256		30	-120	25 / 550	1uA	3.3~6.0	-55~115	TTL	33x18x2
RFM23BP-915	(G)FSK/OOK	915	256		30	-120	25 / 550	1uA	3.3~6.0	-55~115	TTL	33x18x2
<b>Sub-GHz Transmitter Modules</b>												
RFM110W-433	OOK	240~480	30		13		12.4	20nA	1.8~3.6	-55~115	TTL	17.8x12.8x5
<b>Sub-GHz Receiver Modules</b>												
RFM210W-433	OOK	434	10			-108	3.8	60nA		-55~115	TTL	
RFM83C-433	OOK	434	2.5			-108	3	0.9uA	3.6~5.5	-55~115	TTL	32X11x4.3
RFM85W-433	ASK/OOK	434	2.5			-110	3	0.9uA	3.6~5.5	-55~115	TTL	32X11x4.3

For more information, contact:

**AMATEK DESIGN**

[www.amatek.com](http://www.amatek.com)

+61 2 9411 3618

(Sydney, Australia)